

WIDEX MENU™ SUPER POWER BTE MODEL



The MENU classic super power BTE from Widex provides clients with all-round audibility. A 10 channel hearing aid with a strong feature set with an advanced feedback cancellation system that actively reduces feedback.

Moderately-severe to severe-to-profound hearing loss.

- 10 channels
- Flex platform

BASIC FEATURES

- IP58
- Program button
- Volume control button
- Active Feedback Cancellation
- Noise reduction SIS
- Omni directional microphones
- 2 listening programs


ADDITIONAL FEATURES

- Audibility Extender
- Zen
- SmartSpeak
- Sound Diary
- Speech Enhancer
- 3 additional listening programs

ACCESSORIES

- T-DEX
- RC4 Remote Control
- FM/DAI compatible
- T-coil

SUGGESTED FITTING RANGE




ME-SP

MAXIMUM OUTPUT - EAR SIMULATOR

IEC 60118-0


Output dB SPL



MAXIMUM OUTPUT - 2CC COUPLER

IEC 60118-7 / ANSI S3.22-2014


Output dB SPL



OUTPUT - EAR SIMULATOR

IEC 60118-0


Output dB SPL



OUTPUT - 2CC COUPLER

IEC 60118-7 / ANSI S3.22-2014

Output dB SPL



Technical data Typical data obtained through standard pure tone measurements. Hearing aid set to Compass Testmode 1, unless stated otherwise. Measured using a normal hook and standard BTE coupler. For further information, please contact Widex via Widex.com.

		IEC 60118-0	ANSI S3.22-2014 / IEC 60118-7
OSPL90	1600 Hz	137 dB SPL	129 dB SPL
	Peak	143 dB SPL	138 dB SPL
	Average	138 dB SPL	133 dB SPL
Acoustic output (Input 60 dB SPL)	1600 Hz	122 dB SPL	114 dB SPL
	Peak	126 dB SPL	119 dB SPL
	Average	118 dB SPL	115 dB SPL
Full-on gain (Input 50 dB SPL, Compass Full-on gain)	1600 Hz	81 dB	73 dB
	Peak	87 dB	83 dB
	Average	80 dB	76 dB
Telecoil output (Input 31.6 mA/m)	1600 Hz	122 dB SPL	114 dB SPL
	Peak	126 dB SPL	119 dB SPL
	Average	118 dB SPL	115 dB SPL
Frequency range		100 Hz - 5400 Hz	100 Hz - 4950 Hz
Harmonic distortion	500 Hz	< 2%	< 2%
	800 Hz	< 2%	< 2%
	1600 Hz	< 2%	< 2%
Equivalent input noise		21 dB SPL	21 dB SPL
Battery drain (stand by)		0.92 mA	0.92 mA
Battery drain		1.11 mA	1.15 mA
Battery life / hours (Type 675 Zn-Air, 600 mAh)		540 (>460)	520 (>445)
Mobile phone immunity		IRIL: -31/7/2 dB SPL	U-rating: M2 / T2